

CODE: BF-200QG

**NAME:** Backlit Film Premium gloss 200, Eco-Sol.

## **DESCRIPTION:**

- Outstanding brilliance in reflected or transmitted light
- Vibrant colour reproduction
- High rigidity
- Long-term durability & High dimensional stability
- PVC free

## **PROPERTY**

PARAMETER	VALUE		
Base materials	PET		
Thickness/weight	200um		
Coating type	Poly resin coating		
Release paper	-		
Glue type	-		
Finish	GLOSSY(40@60 <sup>o</sup> )		
Lab	94.5, +1.7, -3.5		
Opacity	55%		
Available size	Width: 0.914/1.27/1.52m (36"/50"/60") Up to 3.2m(126")		
	Length: 30m/50m (98'/164')		
Shelf time	12 Months		
Application temperature	-10°C- 65°C (-4F − 150F)		
Durability	Up to 12months		

## **PRINTING INK**

Solvent	Eco-Sol	Aqueous Dye	Aqueous Pigment	UV	Latex
Y	Υ			Y	Υ

## **APPLICATION**

Banne	rs	Backlit	Photographic	Point-of-Sale	Poster	Signage	Transfer
		Υ					

NOTE: All values shown are for reference only. The mentioned data are average of test results and should not be used for the purpose of lawsuit or warranty.

TEL: 86-574-83030100; FAX: 86-574-83030200; EM: INFO@SICOL.CN