

CODE: DSW-17

NAME: DSS Drill Satin Dyesub 202g

DESCRIPTION:

- High density woven fabric, no curling
- Good flatness
- Brilliant color reproduction with Dye & Sub
- Size up to 3.2m
- High density yarns, idea for backlit fabric

PROPERTY

PARAMETER		VALUE
Substrates	Material & Structure	Polyester Woven
	Type of Yarn	DTY 75D x 100D
	Structure	90 x 60
	Shrinkage (MD/CD) ISO 9866.2	≤ 1.50%/ ≤ 0.70%
	Breaking Strength (MD/CD) ISO 13934.1-2013	1090N/1010N
	Tearing Strength (MD/CD) ISO 13937.2-2000	45N/40N
	Elastic (MD/CD) ASTM D 2594 (5.54kgf/101lbf)	≤ 0.6%/ ≤ 0.8%
Coating	Type	Light Dip
	Finish	Matte
Adhesive	Type	-
	Liner	-
Weight (GSM) ASTM D751		202
Opacity		66%
Available size		Up to 3.2m (126")
Fire Retardant Level		M1/B1/NFPA-701 optional
Shelf time (20°C x 50% R.H)		36 Months
Recommend Fixation Temp/Time		-
Durability		12 Months

PRINTING INK

Eco-Sol	UV	Latex	Direct-Sublimation	Heat Transfer	Water base	Screen
	Y		Y	Y		

Y: FULLY COMPATIBLE; Y*: FAIRLY COMPATIBLE OR NEED TO BE VERIFIED

APPLICATION

Events	Blockout	Flags	Trade Show	Displays	Light Box	Wall Mural
			Y		Y	

NOTE: All values shown are for reference only. The mentioned data are average of test results and should not be used for the purpose of lawsuit or warranty.

