

CODE: WP-610CVM

NAME: PolyCanvas Premium, W/R

DESCRIPTION:

- Brilliant color reproduction
- Deep, rich blacks and quick dry
- PES base and no white-scoring
- Splash proof
- Guaranteed for inkjet printing

PROPERTY

PARAMETER		VALUE
Substrates	Material & Structure	Polyester Canvas
	Type of Yarn	600D x 600D
	Structure	warp*2 /weft*1
	Shrinkage (MD/CD) ISO 9866.2	-
	Breaking Strength (MD/CD) ISO 13934.1-2013	420 x 400
	Tearing Strength (MD/CD) ISO 13937.2-2000	20N/18N
	Elastic (MD/CD) ASTM D 2594 (5.54kgf/101lbf)	-
Coating	Type	Porous Coating
	Finish	Matte
Adhesive	Type	-
	Liner	-
Weight (GSM) ASTM D751		300
Opacity		75%
Available size		Up to 3.2m (126")
Fire Retardant Level		M1/B1/NFPA-701 optional
Shelf time (20°C x 50% R.H)		12 Months
Recommend Fixation Temp/Time		-
Durability		12 Months

PRINTING INK

Eco-Sol	UV	Latex	Direct-Sublimation	Heat Transfer	Water base	Screen
	Y				Y	

Y: FULLY COMPATIBLE; Y*: FAIRLY COMPATIBLE OR NEED TO BE VERIFIED

APPLICATION

Events	Blockout	Flags	Trade Show	Displays	Light Box	Wall Mural
						Y

NOTE: All values shown are for reference only. The mentioned data are average of test results and should not be used for the purpose of lawsuit or warranty.

