

CODE: LAM-115G

NAME: Cold Lamination Film Gloss

FEATURES:

- 80um clear monomeric PVC laminates
- Gloss finish
- Idea for protection of indoor graphics

PROPERTY

PARAMETER		VALUE
Film	Material	Clear PVC
	Thickness	65 um
	Finish	Gloss
	E Value %(MD/CD) ASTM882	160%/180%
	Shrinkage/mm(MD/CD) FTM-14	0.38/0.28
Glue	Type	Solvent clear acrylic glue
	Thickness	15 um
	Init Tac 20min peel (N/in) FTM-9	8N
	Hold (9.8N/in ²)	≥ 24hours
	180°Peel (N/in) FTM-1	10N
Liner	Liner type	White paper green grids
	Weight(Thickness)	84 gsm
Available size	Width	0.914/1.07/1.27/1.37/1.52m (36"/42"/50"/54"/60")
	Length	50m (55Yd)
Shelf time (20oC x 50% R.H)		12 Months
Applying temperature Range °C		5~40°C
Durability		12 Months indoor

APPLICATION

Indoor	Outdoor	UV	Vehicle Wrapping	Photo Graphic	Floor Graphic
Y					

NOTE: All values shown are for reference only. The mentioned data are average of test results and should not be used for the purpose of lawsuit or warranty.