

CODE: LAM-8100UM

NAME: Cold Lamiantion Premuim(OT) Ultra Matte

FEATURES:

- 100um Optical clear monomeric PVC laminates
- Ultra Matte finish
- High clarity PVC enhances appearance of digital images.
- Up to 24months protection of graphics from abrasion and moisture.
- Suitable for use over all digital inks printed graphics Retards color fade caused by UV light.

PROPERTY

PARAMETER		VALUE
Film	Material	Optical Clear PVC
	Thickness	80 um
	Finish	Ultra Matte
	E Value %(MD/CD) ASTM882	190%/210%
	Shrinkage/mm(MD/CD) FTM-14	0.25/0.18
Glue	Type	Solvent clear acrylic glue
	Thickness	20 um
	Init Tac 20min peel (N/in) FTM-9	11N
	Hold (9.8N/in ²)	≥ 48hours
	180°Peel (N/in) FTM-1	13N
Liner	Liner type	Kraft paper (Blue grids)
	Weight(Thickness)	100 gsm
Available size	Width	0.914/1.07/1.27/1.37/1.52m (36"/42"/50"/54"/60")
	Length	50m (55Yd)
Shelf time (20oC x 50% R.H)		24 Months
Applying temperature Range °C		-10 ~65°C
Durability		24 Months indoor

APPLICATION

Indoor	Outdoor	UV	Vehicle Wrapping	Photo Graphic	Floor Graphic
Y	Y				

NOTE: All values shown are for reference only. The mentioned data are average of test results and should not be used for the purpose of lawsuit or warranty.