

CODE: LAM-FM

NAME: Flooring Graphic Lamination

FEATURES:

- 195um clear monomeric PVC laminates
- Sand(R10) finish
- Textured lustex finish PVC for indoor and short term outdoor walkway graphics
- Cost effective promotion laminate solution

PROPERTY

PARAMETER		VALUE
Film	Material	Clear PVC
	Thickness	170 um
	Finish	Sand(R10)
	E Value %(MD/CD) ASTM882	260%/290%
	Shrinkage/mm(MD/CD) FTM-14	0.24/0.20
Glue	Type	Solvent clear acrylic glue
	Thickness	25 um
	Init Tac 20min peel (N/in) FTM-9	12N
	Hold (9.8N/in ²)	≥ 48hours
	180°Peel (N/in) FTM-1	14N
Liner	Liner type	SPE white paper
	Weight(Thickness)	140 gsm
Available size	Width	0.914/1.07/1.27/1.37/1.52m (36"/42"/50"/54"/60")
	Length	30m/50m (33Yd/55Yd)
Shelf time (20oC x 50% R.H)		24Months
Applying temperature Range °C		-10 ~65°C
Durability		24 Months indoor

APPLICATION

Indoor	Outdoor	UV	Vehicle Wrapping	Photo Graphic	Floor Graphic
Y	Y				Y

NOTE: All values shown are for reference only. The mentioned data are average of test results and should not be used for the purpose of lawsuit or warranty.